

READY MIXED FILLER

A smooth, ready mixed water based filler, ideal for small crack repairs and making good minor surface defects. Suitable for interior and exterior use on masonry, woodwork and most types of building substrates.

AVAILABILITY

Colour range White.

Packaging 1kg plastic container.

PROPERTIES

Drying time 1-2 hours depending on thickness.

Composition Pigments, reinforcing fillers & styrene acrylic copolymer.

Spreading rate Variable depending on width and depth of filling or making good.

Wet thickness As required up to a maximum of 7mm per application.

Volume solids Not applicable.

Flash point Not applicable.

VOC content Not applicable.

Limitations Do not apply when there is a risk of rain, or when air or substrate temperatures are likely to fall below 8°C.

PREPARATION

New surfaces All surfaces must be sound, suitably dry and free from anything that will interfere with the adhesion of the materials to be applied.

Previously decorated surfaces

All surfaces must be sound, suitably dry and free from anything that will interfere with the adhesion of the materials to be applied. Remove all loose, and failing or suspect material.

APPLICATION Apply using a filling knife. Fill all cracks, open joints and small surface defects with Sandtex Trade Ready Mixed Filler, remove surplus material, finish to match existing and allow to dry.

CLEANING Wash equipment with clean water immediately after use. Do not empty or wash the remains of Sandtex Trade Ready Mixed Filler into drainage systems

HEALTH AND SAFETY

Please refer to the Safety, Health and Environmental Information on the container. Take special precautions during the surface preparation of pre 1960's painted surfaces as they may contain harmful lead. For further information contact the Customer Relations Team.

When preparing the surfaces avoid the inhalation of dust and/or metal particles. Wear a suitable facemask. Material Safety Data Sheets for this and all other Sandtex products are freely available from the place of purchase or the address below. Store in secure dry

conditions inaccessible to children or animals. Containers should be kept closed during storage. Do not empty into drains, watercourses or access routes to septic tanks.

GENERAL INFORMATION

Apply all products in accordance with BS 6150: 2006 Code of practice for painting of buildings and BS 8000: Part 12: 1989 Code of practice for decorative wallcoverings and painting. Under normal and frost free conditions this product will remain usable for up to two years if stored correctly and unopened.

Every care is taken to ensure that all information provided on this Technical Data Sheet is accurate. Final results cannot be guaranteed by the manufacturer as it has no control over the conditions under which its products are applied.

For help or more information contact our Customer Relations Team on 0330 0240 302. Before using this product please ensure you have the latest information. The information is correct at date of issue April 2015.



Sandtex Trade

Hollins Road, Darwen, Lancs BB3 0BG

Tel: 0330 0240 302 Fax: 0330 0240 279 Email: info@sandtextrade.co.uk

Website: www.sandtextrade.co.uk